

GLOBAL

LP 9971 - TD

LP 9974 - TD

LP 9971 - TD / AUT

**1 - NEEDLE / 2 - NEEDLE, POST-BED
INDUSTRIAL SEWING
MACHINE**

INSTRUCTION MANUAL SPARE PARTS LIST

Global International BV

H. Figeeweg 4
2031 BJ Haarlem
tel: 023-5319584
fax: 023-5311022
e-mail: global@imca.net


Global Parts by

H. Figeeweg 4B
2031 BJ Haarlem
tel: 023-5425312
fax: 023-5423422
e-mail: globalparts@planet.nl

| | |
|--|-------|
| Main parts name of machine head | |
| 1. Single needle post-bed driven roller sewing machine..... | 1 |
| 2. Double needles post-bed driven roller sewing machine..... | 2 |
| Preparation for installation of Machine | |
| 1. Working table..... | 3 |
| 2. How to install the hinge bracket and anti-vibration rubber..... | 3 |
| 3. How to mount the machine head on the table..... | 4 |
| 4. How to adjust the bolt..... | 4 |
| 5. How to mount the bobbin winder assembly..... | 5 |
| 6. How to mount the thread stand assembly..... | 5 |
| 7. How to connect the foot pedal and motor lever..... | 6 |
| 8. How to mount the belt guard..... | 6 |
| 9. How to mount the foot lifter mechanism..... | 6 |
| Preparation for operation | |
| 1. Thread selection..... | 7 |
| 2. How to attach the needle..... | 7 |
| 3. How to remove the bobbin from the hook..... | 8 |
| 4. How to wind the thread on the bobbin..... | 8 |
| 5. How to adjust bobbin winder..... | 8 |
| 6. How to place the bobbin into the hook..... | 9 |
| 7. How to lead the bottom thread..... | 9 |
| 8. How to lead the upper thread..... | 10 |
| 9. How to use the back tacking stitch..... | 11 |
| Adjustment | |
| 1. Adjustment of stitch length..... | 12 |
| 2. Thread tension..... | 12 |
| 3. Adjustment the pressure of presser foot..... | 12 |
| 4. Thread tension adjustment..... | 13 |
| 5. The roller foot height adjustment..... | 14 |
| 6. Lower feeding roller adjustment..... | 14 |
| 7. Feeding speed adjustment..... | 15 |
| 8. The position of the needle and hook adjustment..... | 15 |
| 9. Adjustment of tip of hook..... | 16 |
| 10. Adjustment the position of the fixed knife base..... | 16 |
| 11. Adjustment of the thread cutting knife position..... | 16 |
| 12. The position of the thread cutting knife and needle plate..... | 17 |
| 13. Adjustment of the cam of the thread cutting knife..... | 17 |
| Maintenance and trouble inspection | |
| 1. Cleaning..... | 18 |
| 2. Lubrication..... | 18 |
| 3. Trouble examination..... | 18,19 |


MAIN PARTS / NAME OF MACHINE

LP 9971 TD; LP 9971 TD-AUT Series / Single needle post-bed driven roller sewing machine



- | | |
|--------------------------------------|--------------------------|
| 1. Spool pin | 11. Post Cap |
| 2. 4 Holes thread retainer | 12. Needle plate bracket |
| 3. Thread tension regulator assembly | 13. Stitch regulator |
| 4. Thread take-up guard | 14. Balance wheel |
| 5. Thread take-up lever | 15. Thread guide |
| 6. Thread retainer | 16. Adjustment screw |
| 7. Presser bar | 17. Belt guard |
| 8. Upper feeding roller | 18. Lower feeding roller |
| 9. Face plate | 19. Needle plate |
| 10. Side bracket | |

2. LP 9974 TD / Double needles post-bed driven roller sewing machine




1. Spool pin
2. 4 Holes thread retainer
3. Thread tension regulator assembly
4. Thread take-up guard
5. Thread take-up lever
6. Thread retainer
7. Presser bar
8. Upper feeding roller
9. Face plate
10. Side bracket

11. Post cap
12. Needle plate bracket
13. Stitch regulator
14. Balance wheel
15. Needle lamp
16. Adjustment screw
17. Belt Guard
18. Lower feeding roller
19. Needle plate



PREPARATION FOR INSTALLATION OF MACHINE

1. Working table




2. How to install the hinge bracket and anti-vibration rubber

- (1) Insert the pin (2) into the bracket (1), as shown in fig A.
- (2) Fit the hinge bracket (1) on to the working table (3) to be fixed by the nails.
- (3) Fit the anti-vibration rubber (4) on to the corners of the machine head location on the table, as shown in fig B.




3. How to mount the machine head on to the table

- 1) Fit the hinges (3) into the holes on the machine head base.
- 2) Set the machine head on to the working table (1)
- 3) The groove of the hinge must aim at the hinge pin of bracket (2)
- 4) The machine head must be identical into the hinge bracket and anti-vibration rubber




4. How to adjust the belt

- 1) The machine turns anti-clock wise
- 2) Fit the belt on the pulley (2) of the motor (6) and the balance wheel (3) of the machine head (1)
- 3) Adjust the belt tension by press the belt (7) and adjust the screw cap (4) off the motor fixed bolt (5)
- 4) Then press the belt again (as fig.2) the pressed depth about 10mm-20mm is the best situation.




5. How to mount the bobbin winder

- 1) The bobbin winder assembly is installed on the table under the balance wheel of the machine head
- 2) Push the press plate (4) to check the pulley (2) contact with the belt (1) of not
- 3) Use 2 pieces of the screw (3) to fix the bobbin winder on the working table




6. How to mount the thread stand assembly

- 1) The thread stand is fitted on the working table (2) in the right rear end of the machine head
- 2) The screw end of the arm (3) is inserted into the hole on the working plate
- 3) Then tight the screw cap (1) on the arm




7 How to connect the foot pedal and motor lever.

- 1) The foot pedal operation likes the start switch of the motor, forward is in sewing and back ward is in thread cutting (please refer to the motor operation manual)
- 2) The best angle of the foot pedal (2) installation is 30-40
- 3) The angle of the foot pedal can be adjusted by loosening the adjustment screw (1), as shown in fig.5




8. How to mount the belt guard

- 1) The belt guard (2) prevent the operator from hurting by the belt (1) during operation
- 2) Fix the belt guard on the machine head by 2 pieces of screws (3)



9. How to mount the foot lifter mechanism

- 1) Please refer to the parts drawing for the assembly of the foot lifter mechanism
- 2) Mount the foot lifter mechanism under the machine head base right end, as shown in fig. 7
- 3) Push the knee plate (2) to right side to lift the press foot or push the foot pedal backward slightly to carry the auto control box (3) for foot lifter



PREPARATION FOR OPERATION

1. Thread selection

For best result, use the high quality sewing thread.
Suggest use the left-twist thread/




Fig8

2. How to attach the needle

The needle type DP x 5 (135x5) is recommendable for general usage

- 1) Turn the balance wheel to raise the needle bar (3) to its highest position
- 2) Move the roller foot (1) to upon and left finally
- 3) Loosen the needle clamping screw (4)
- 4) Hold the needle to its sides with the long groove side and insert onto the needle clamp
- 5) Tighten the needle clamping screw (4)


- If the stitch jump or wrap happens by using the silk thread or nylon thread, then slope the needle hole slightly to solve it.



3. How to remove the bobbin from the hook

- 1) Turn the balance wheel to raise the needle bar to its highest position
- 2) Move the roller foot to the left
- 3) Open the post cap
- 4) Turn up the latch lever (1)
- 5) Remove the bobbin case (3) and bobbin (4) from the hook (2)

Fig10



4. How to wind the lower thread on the bobbin

- 1) Fit the bobbin (1) into the bobbin pin B
- 2) Push the lever D down ward
- 3) The thread (2) from the spool through the hole (3) of the thread guide to the intension disc (4). Wind the end of the thread through the tension disc on the bobbin (1) 2-3 times.
- 4) If the thread winded uneven then loosen the screw A to adjust the thread guide




Fig11

5. How to adjust bobbin winder assembly

- 1) In the event of uneven winding toward the left, loosen the screw (A) of the thread guide and adjust it moving the thread guide slightly to the right
- 2) In the event of uneven winding toward the right, adjust it moving the guide to the left
- 3) When the thread (particularly nylon thread) is wound too tightly, adjust the pressure of the tension disc with nut (5) so that thread can be pulled out smoothly.
- 4) In the event of excessive winding, turn the screw (5) to the left, and to the right when insufficient.
- 5) It is desirable that the bobbin is winded evenly with thread and improper winding in Fig. 12

Fig12



Correct

Error

Error

6. How to place the bobbin into the hook

- 1) Turn the balance wheel to raise the needle bar to its highest position
- 2) Move the roller to the left
- 3) Open the post cap
- 4) Turn up the latch lever (3)
- 5) Place the bobbin (2) into the hook (4)
- 6) Set the bobbin case (1) and flap down the latch lever
- 7) Close the post cap in fig 13




Fig13

7. How to lead the lower thread

- 1) Fit the bobbin (2) into the bobbin case (1)
- 2) Insert the pulled out thread through the slit (A)
- 3) Loosen the adjustment screw (3) and the thread will pass through tension spring (4) as shown in fig. 14
- 4) The thread is inserted through the hole (B) and pulled out about 50mm in length as show in fig.15





Fig15

Fig14

8. How to lead the upper thread (Fig 16, 17)

- 1) Turn the balance wheel to raise the thread take-up lever to its highest position
- 2) Raise the presser bar and turn the roller foot to left
- 3) Thread in the following process
- 4) The thread pass through the spool pin (1) first
- 5) 4 holes thread retainer (2)
- 6) Thread tension regulator assembly
- 7) Tension spring (4)
- 8) Thread take -up lever (5)
- 9) Thread guide (6)
- 10) Thread tension bar (7)
- 11) Thread Guide (8)
- 12) Needle (9)



Single needle
Fig16





Fig17

Double Needles

9. Back tacking operation


- 1) Push on the red button (6) to start the back tacking processing as the fig. 18 shows
- 2) It is also operated by the foot paddle to process the back tacking as the fig (18-1) shows.

Fig 18



Red button

Fig 18-1



High speed
Low speed
Stop
Back tacking
Thread cut



Low speed



High speed



Stop



Back tacking



Thread cut

ADJUSTMENT

1. Adjustment of stitch length

- 1) The balance wheel (1) had the stitch scale (3)
- 2) Push on the stitch regulator (2) and turn the balance wheel
- 3) Turn the stitch scale required to the arrow mark (4)
- 4) Lose the stitch regulator to complete the stitch adjustment





Fig19

2. Thread tension



3. Adjustment the pressure of presser foot

- 1) The thickness of the sewed material affect the presser foot pressure
- 2) The pressure of presser foot adjustment by the adjustment screw on the machine lead




Fig23

4. Thread tension adjustment

- 1) Turn the nut of the thread tension regulator (1) to adjust. The upper thread tension if necessary during sewing as shown in fig. 26
- 2) The lower thread tension is affected by the thread type and sewed material, so turn the adjustment screws (2), as shown in fig. 25 to meet the requirement
- 3) The spring (3) adjustment limit is about 5mm-10mm as shown in fig. 26. The spring tension is adjusted by the tension nut (5)
- 4) Adjustment spring pin (6) should be on the centre for the standard adjustment. Lose the screw (2) and turn the adjustment spring pin (6) to adjust the tension as show in fig. 27




Fig24



Fig25




Fig26





Fig27

5. The roller foot height adjustment

- 1) Lose screw
- 2) Remove the face plate
- 3) Turn the presser foot lever (2) to raise the presser foot
- 4) Lose screw (1) to lift up or down the presser bar for presser foot (3) adjustment. The highness is above the needle plate 11mm, as fig. 28 shows.



6. Lower feeding roller adjustment

- 1) For single needle, lose the set screws (2). Use the flat screw driver to turn the cam shaft (1) for the roller highness adjustment shown in fig. 29.
- 2) For double needle lose the screw (3) to adjust the highness of roller, shown in fig.30
 - a) The highness for thin material sewed is 0.8 mm in normal. The material will be damaged if the roller was too high
 - b) The highness for thick material sewed is 1.2 mm. The stitch will be uneven if the roller was too low
 - c) The highness for general material sewed is 1mm




Fig29

Single needle feeding gear




Fig30


Double Needle feeding gear

7. Feeding speed adjustment

The speed of upper roller and feed dog is not synchronous will cause the uneven stitch between the upper and lower thread.

Adjust the upper roller to improve



- 1) Lose screw (1) and turn the link (2) up for fast and down for slow to adjust the roller speed.



8. The position of the needle and hook adjustment

The quality of stitches is based on the synchronous position of the tip of hook and the needles as fig. 32, 32 shows.

- 1) To lose the needle bar to make the lowest of needle position. The distance is 3.0 mm between the upper side of needle hole and the tip of hook, and tighten the needle bar, as fig 32 (A)
- 2) To rise the needle bar from the lowest of needle position, the distance is 2.5 mm tighten it when it is on the position of tip of hook and the centre line of needle
- 3) The clearance is within 0.05mm between the needle and tip of hook. The clearance is 0.05-0.1mm between the needle and the needle guard washer. Must adjust it again when change needles.



9. Adjustment of the fillister of needle plate and projection of bobbin case

- 1) The fixed groove under the needle plate (1) is used to fix the bobbin case (2) to prevent its rotation
- 2) The fitting position between the fillister of needle plate and the projection of bobbin case is 1.4 mm




Fig34

10. Adjustment the position of the fixed knife

- 1) Set the fixed knife (3) on the knife holder (2)
- 2) Lose screw (1) and place the thread cutting knife (4) on the fixed knife carefully
- 3) Adjust the distance between the fixed knife and needle hole to 5mm.
- 4) Turn the balance wheel to check the knife is contacted by the fixed knife or not when it came to the ready position for thread cutting.




Fig35

11. Adjustment of the thread cutting knife position

- 1) Place the cutting knife (1) on the ready position
- 2) As shown in fig.36 the distance between the top of the knife and the end of fixed knife is about 1.5mm
- 3) Tighten the screw





Fig36


12. The position of the thread cutting knife and needle plate

- 1) Adjust the highness of the cutting knife
- 2) Lose screw to move the highness of cutting knife shaft.
- 3) The gap between the cutting knife and needle plate is about 1.5mm



13. Adjustment of the came of the thread cutting knife

- 1) The cam (1) is used for cutting knife timing adjustment
 - 2) Lose the set screw and turn the cam to adjust the thread cut time.
 - 3) Fix the cam and turn the shaft to watch the thread cut status
- Please check does the knife contact the slide plate when it rotates to the bottom.



MAINTENANCE AND TROUBLE INSPECTION

1. Cleaning

The teeth of feed dog, hook, upper thread tension regulator disc and thread controller discs are often covered by dust and lint causing improper operation and uneven stitching. Therefore, clean as often as necessary.

2. Lubrication

- 1) Suggest use Mobil #10, Esso #32 or same grade lubricate oil
- 2) Lubricate the machine 2-3 times a week
- 3) Lubricate the portion as the arrow indicated on the fig.39




Fig39

3. Trouble examination

- 1) Balance wheel can not turn 1. Power unconnected 2. The pulse of brake failed
 - 2) Upper or lower thread cut; 1. Needle end bend 2. Needle blunt 3. Improper needle attachment 4. Improper threads lead 5. Rotating hook needs lubrication 6. Rotating hook is covered by dust or thread.
 - 3) Uneven stitch: 1. press foot pressure is too weak 2. Feeding roller is too low 3. bobbin case broken
 - 4) Stitch jump 1. Needle head bend 2. Improper needle attachment 3. Presser foot pressure is too weak 4. Improper threading 5. Needles blunt 6. Sewing speed is too fast.
 - 5) Thread tension is not enough: 1. adjustment spring lost 2. Bobbin case broke 3. improper threading
 - 6) Needle broken: 1. needles blend 2. needle does not properly pass through the centre of the hole on the feeding roller
- If you are unable to solve the trouble in accordance with the above-mention methods, then switch off the power and contact with the local distributors.

GLOBAL

LP 9971 - TD

LP 9974 - TD

LP 9971 - TD / AUT

1 - NEEDLE / 2 - NEEDLE, POST-BED
INDUSTRIAL SEWING
MACHINE

SPARE PARTS LIST


Global International BV

H. Figeeweg 4
2031 BJ Haarlem
tel: 023-5319584
fax: 023-5311022
e-mail: global@imca.net

Global Parts bv

H. Figeeweg 4B
2031 BJ Haarlem
tel: 023-5425312
fax: 023-5423422
e-mail: globalparts@planet.nl

MAIN FRAME AND COVER PARTS




MAIN FRAME AND COVER PARTS

| Ref. No | Part No. | Name of Part | Amt. req. | | Remarks |
|---------|-------------|------------------------|-----------|------|---------|
| | | | 9971 | 9974 | |
| 1 | MS-119687 | Face Plate | 1 | 1 | |
| 2 | MS-108246 | Screw | 1 | 1 | |
| 3 | MS-108234 | Screw | 1 | 1 | |
| 4 | MS-168061 | Thread Take-up Cover | 1 | 1 | |
| 5 | MS-210210 | Screw | 1 | 1 | |
| 6 | MS-119027 | 4 Hole Thread Retainer | 1 | 1 | |
| 7 | MS-314946 | Screw | 1 | 1 | |
| 8 | MS-119039 | Arm Side Cover | 1 | 1 | |
| 9 | MS-700335 | Screw | 2 | 2 | |
| 10 | MS-118430 | Thread Guide Wire | 1 | 1 | |
| 11 | MS-700335 | Screw | 1 | 1 | |
| 14 | MS-119686 | Thread Guide Wire | 1 | 1 | |
| 15 | MS-700335 | Screw | 1 | 1 | |
| 16 | MS-119092 | Bracket | 1 | 1 | |
| 17 | MS-108285-1 | Screw | 2 | 2 | |
| 18 | MS-119091 | Bottom Cover | 1 | 1 | |
| 19 | MS-108225 | Screw | 5 | 5 | |

ROLLER PRESSER FOOT MECHANISM FOR 9971 9974

輪錢組機構




ROLLER PRESSER FOOT MECHANISM FOR 9971 9974

輪錢組機構

| Ref. No | Part No. | Name of Part | Amt. req. | | Remarks |
|---------|-------------|---------------------------------|-----------|------|---------|
| | | | 9971 | 9974 | |
| 1 | MS-119803 | Roller Presser Assy. (Large) | 1 | 1 | |
| 2 | MS-119803-1 | Roller Presser Assy. (Middle) | 1 | 1 | |
| 3 | MS-119802 | Roller Presser Assy. (Small) | 1 | 1 | |
| 4 | MS-119469 | Spring Washer | 1 | 1 | |
| 5 | MS-033145 | Pin | 1 | 1 | |
| 6 | MS-175109 | Gear | 1 | 1 | |
| 6-1 | MS-175109-1 | Gear Presser Shaft | 1 | 1 | |
| 6-2 | MS-175109-2 | Gear | 1 | 1 | |
| 6-3 | MS-175109-3 | Gear Presser Shaft Seat (Front) | 1 | 1 | |
| 6-4 | MS-175109-4 | Gear Presser Shaft Seat | 1 | 1 | |
| 6-5 | MS-175109-5 | Ball | 1 | 1 | |
| 6-6 | MS-175109-6 | Screw | 1 | 1 | |
| 6-7 | MS-175109-7 | Screw | 1 | 1 | |
| 7 | MS-175107 | Gear | 1 | 1 | |
| 7-1 | MS-175107-1 | Gear Presser Shaft | 1 | 1 | |
| 7-2 | MS-175107-2 | Gear | 1 | 1 | |
| 7-3 | MS-175107-3 | Gear Presser Shaft Seat | 1 | 1 | |
| 8 | MS-175108 | Gear | 1 | 1 | |
| 8-1 | MS-175108-1 | Gear Presser Shaft | 1 | 1 | |
| 8-2 | MS-175108-2 | Gear | 1 | 1 | |
| 8- | MS-175108-3 | Gear Presser Shaft Seat | 1 | 1 | |
| 9 | MS-664290 | Retaining Ring | 1 | 1 | |
| 10 | MS-133116 | Ball Bearing | 1 | 2 | |
| 10-1 | MS-133116-1 | Washer | 1 | 1 | |
| 11 | MS-518210 | Retaining Ring | 1 | 1 | |
| 12 | MS-119953 | Roller Presser Bracket | 1 | 1 | |
| 13 | MS-119943 | Roller Presser Bracket | 1 | 1 | |
| 14 | MS-119956 | Roller Presser Bracket | 1 | 1 | |
| 15 | MS-210043 | Screw | 1 | 1 | |
| 16 | MS-119491 | Washer | 1 | 1 | |
| 17 | MS-119807 | Guide Seat | 1 | 1 | |
| 18 | MS-119955 | Guide Seat | 1 | 1 | |
| 19 | MS-119954 | Guide Seat | 1 | 1 | |
| 20 | MS-173174 | Screw | 2 | 1 | |


THREAD TAKE- UP LEVER MECHANISM



THREAD TAKE- UP LEVER MECHANISM

| Ref. No | Part No. | Name of Part | Amt. req. | | Remarks |
|---------|------------------|---------------------------------|-----------|------|---------|
| | | | 9971 | 9974 | |
| 1 | MS-118084 | Thread Take-up Assy | 1 | 1 | (2~19) |
| 2 | MS-119009 | Take-up Lever Support Stud | 1 | 1 | |
| 3 | MS-168039 | Washer | 2 | 2 | |
| 4 | MS-215022 | Needle Bearing | 2 | 2 | |
| 5 | MS-119008 | Take-up Frame | 1 | 1 | |
| 6 | MS-119762 | Take-up Crank Pin | 1 | 1 | |
| 7 | MS-119049 | Bushing | 1 | 1 | |
| 8 | MS-119007 | Take-up Lever | 1 | 1 | |
| 9 | MS-167569 | Ball Bearing | 1 | 1 | |
| 10 | MS-167570 | Ball Bearing | 1 | 1 | |
| 11 | MS-119006 | Take-up Lever | 1 | 1 | (7~10) |
| 12 | MS-168046 | Washer | 1 | 1 | |
| 13 | MS-168047 | Screw | 1 | 1 | |
| 14 | MS-610210 | Retaining Ring | 2 | 2 | |
| 15 | MS-039177 | Screw | 1 | 1 | |
| 16 | MS-119013 | Needle Bar Connecting Stud | 1 | 1 | |
| 17 | MS-119765 | Needle Bar Connecting Crank Rod | 1 | 1 | |
| 18 | MS-119763 | Washer | 1 | 1 | |
| 19 | MS-218080 | Needle Bearing | 1 | 1 | |
| 20 | MS-118518 | Needle Bar Guide Slide Block | 1 | 1 | |
| 21 | MS-168041 | Bushing | 1 | 1 | |
| 22 | MS-314220 | Screw | 3 | 3 | |


UPPER SHAFT AND BALANCE WHEEL MECHANISM



UPPER SHAFT AND BALANCE WHEEL MECHANISM

| Ref. No | Part No. | Name of Part | Amt. req. | | Remarks |
|---------|-------------|----------------------|-----------|------|---------|
| | | | 9971 | 9974 | |
| 1 | MS-119702-2 | Crank Cam | 1 | 1 | |
| 2 | MS-130224 | Screw | 2 | 2 | |
| 3 | MS-119702-3 | Screw | 1 | 1 | |
| 4 | MS-119702-4 | Screw | 1 | 1 | |
| 5 | MS-700510 | Screw | 1 | 1 | |
| 6 | MS-119702-5 | Bushing | 1 | 1 | |
| 7 | MS-119702-1 | Upper Shaft | 1 | 1 | |
| 7-1 | MS-119702 A | Upper Shaft Assy | 1 | 1 | |
| 8 | MS-119702-6 | Bushing | 0 | 1 | |
| 9 | MS-018643 | Ball Bearing | 1 | 1 | |
| 10 | MS-069160 | Timing Belt | 1 | 1 | |
| 10-1 | MS-069160-1 | Timing Belt | 1 | 1 | |
| 11 | MS-119707 | Timing Belt Wheel | 2 | 2 | |
| 12 | MS-335902 | Screw | 2 | 2 | |
| 13 | MS-335902-1 | Screw | 6 | 6 | |
| 14 | MS-016153 | Ball Bearing | 2 | 2 | |
| 15 | MS-119705 | Upper Shaft Bushing | 2 | 2 | |
| 16 | MS-069746 | bushing | 1 | 1 | |
| 17 | MS-168480 | Washer | 2 | 2 | |
| 18 | MS-210265 | Screw | 1 | 1 | |
| 19 | MS-175048 | Feed Regulator Scale | 1 | 1 | |
| 20 | MS-170913 | Pulley Balance Wheel | 1 | 1 | |
| 21 | MS-341902 | Screw | 2 | 2 | |
| 22 | MS-210287 | Screw | 1 | 1 | |


UPPER SIDE SHAFT MECHANISM



UPPER SIDE SHAFT MECHANISM

| Ref. No | Part No. | Name of Part | Amt. req. | | Remarks |
|---------|------------------|----------------------|-----------|------|---------|
| | | | 9971 | 9974 | |
| 1 | MS-119164 | Clamp | 1 | 1 | |
| 2 | MS-108177 | Screw | 1 | 1 | |
| 3 | MS-119163 | Crank | 1 | 1 | |
| 4 | MS-108225 | Screw | 1 | 1 | |
| 5 | MS-119085 | Washer | 1 | 1 | |
| 6 | MS-119511 | Upper Side Shaft | 1 | 1 | |
| 7 | MS-118600 | Bushing | 2 | 2 | |
| 8 | MS-215124 | Needle Bearing | 2 | 2 | |
| 9 | MS-133283 | Washer | 2 | 2 | |
| 10 | MS-118504 | Collar | 1 | 1 | (11) |
| 11 | MS-118503 | Screw | 1 | 1 | |
| 12 | MS-610370 | Retaining ring | 1 | 0 | |
| 13 | MS-119042-2 | Eccentric With Rod | 1 | 0 | |
| 14 | MS-215028 | Needle Bearing | 1 | 0 | |
| 15 | MS-175150 | Pin | 1 | 0 | |
| 16 | MS-242810 | Needle Bearing | 1 | 0 | |
| 17 | MS-119042 | Crank With Eccentric | 1 | 1 | |
| 18 | MS-108225-2 | Screw | 1 | 1 | |
| 19 | MS-130224 | Screw | 1 | 1 | |


NEEDLE BAR MECHANISM



NEEDLE BAR MECHANISM

| Ref. No | Part No. | Name of Part | Amt. req. | | Remarks |
|---------|-------------------|----------------------------|-----------|------|----------|
| | | | 9971 | 9974 | |
| 1 | MS-118197 | Needle Bar | 0 | 1 | |
| 2 | MS-118196 | Ring Clamp | 0 | 1 | |
| 3 | MS-108174-1 | Screw | 0 | 1 | |
| 4 | MS-700868 | Screw | 0 | 1 | |
| 5 | MS-700868-1 | Screw | 0 | 1 | |
| 6 | MS-118195 | Needle Holder (2,8) | 0 | 1 | (4, 5) |
| | MS-118195-1 | Needle Holder (2.4) | 0 | 1 | (4, 5) |
| | MS-118195-2 | Needle Holder (3.2) | 0 | 1 | |
| 7 | MS-175096 | Needle Bar | 1 | 0 | |
| 8 | MS-174173 | Screw | 1 | 0 | |
| 9 | MS-175096-2 | Thread Guide | 1 | 0 | |
| 10 | MS-175150 | Pin | 1 | 1 | |
| 11 | MS-215028 | Needle Bearing | 2 | 2 | |
| 12 | MS-169137 | Washer | 2 | 2 | |
| 13 | MS-305305 | Screw | 2 | 2 | |
| 14 | MS-024191 | Nut | 2 | 2 | |
| 15 | MS-118612 | Pin | 1 | 1 | |
| 16 | MS-119718 | Shaft | 1 | 1 | |
| 17 | MS-030310 | Pin | 1 | 1 | |
| 18 | MS-119046 | Connecting Rod | 1 | 1 | |
| 19 | MS-119525-2 | Washer | 1 | 1 | |
| 20 | MS-119718-2 | Retaining Ring | 1 | 1 | |
| 21 | MS-118858 | Spring Plate | 1 | 1 | |
| 22 | MS-108285 | Screw | 1 | 1 | |
| 23 | MS-118857 | Spring | 1 | 1 | |
| 24 | MS-118543 | Crank | 1 | 1 | |
| 25 | MS-118544 | Pin | 1 | 1 | (24, 25) |
| 26 | MS-118543A | Crank Shaft | 1 | 1 | |
| 27 | MS-640150 | E-Ring | 1 | 1 | |
| 28 | MS-020490 | Spring Plate | 1 | 1 | |
| 29 | MS-130224 | Screw | 2 | 2 | |
| 29-1 | MS-130224-1 | Screw | 1 | 1 | |
| 30 | MS-134356 | Needle | 1 | 1 | |
| 31 | MS-118545 | Washer | 1 | 1 | |


NEEDLE BAR FEED MECHANISM



NEEDLE BAR FEED MECHANISM

| Ref. No | Part No. | Name of Part | Amt. req. | | Remarks |
|---------|-------------|-----------------------------------|-----------|------|---------|
| | | | 9971 | 9974 | |
| 1 | MS-118600 | Bushing | 2 | 0 | |
| 2 | MS-215124 | Needle Bearing | 2 | 0 | |
| 3 | MS-133283 | Washer | 4 | 0 | |
| 4 | MS-118610 | Crank | 1 | 0 | |
| 5 | MS-108285-1 | Screw | 1 | 0 | |
| 6 | MS-130224 | Screw | 1 | 0 | |
| 8 | MS-118594 | Needle Bar Connecting Link Guide | 1 | 1 | |
| 9 | MS-100355 | Screw | 2 | 2 | |
| 10 | MS-119014 | Oil Felt | 1 | 1 | |
| 11 | MS-119015 | Holder | 3 | 3 | |
| 12 | MS-706169 | Screw | 2 | 2 | |
| 13 | MS-119940 | Needle Bar Holder | 1 | 1 | |
| 14 | MS-119940-5 | Needle Bar Bushing | 1 | 1 | |
| 15 | MS-119940-4 | Needle Bar Bushing | 1 | 1 | |
| 16 | MS-118521 | Needle Bar Support Frame Retainer | 0 | 1 | |
| 17 | MS-108219 | Screw | 0 | 1 | |
| 18 | MS-118520 | Bushing | 0 | 1 | |
| 19 | MS-314286 | Screw | 0 | 1 | |
| 20 | MS-118520-1 | Bushing | 0 | 1 | |
| 21 | MS-118503 | Screw | 1 | 1 | |
| 22 | MS-118504 | Collar | 1 | 1 | (21) |

PRESSER FOOT BAR MECHANISM




MS-049657 3/32"

MS-049657-1 1/16"

PRESSER FOOT BAR MECHANISM

| Ref. No | Part No. | Name of Part | Amt. req. | | Remarks |
|---------|-------------------|------------------------------|-----------|------|---------|
| | | | 9971 | 9974 | |
| 1 | MS-119019 | Presser Bar Bushing (Upper) | 1 | 1 | |
| 2 | MS-700785 | Screw | 1 | 1 | |
| 3 | MS-119018 | Presser Bar | 1 | 1 | |
| 3-1 | MS-119018-1 | Pin | 1 | 1 | |
| 4 | MS-118530 | Presser Bar Holder | 1 | 1 | |
| 5 | MS-700510 | Screw | 2 | 2 | |
| 6 | MS-119019-1 | Presser Bar Bushing (Lower) | 1 | 1 | |
| 7 | MS-700510-1 | Screw | 1 | 1 | |
| 8 | MS-119165-1 | Roller Presser Holder | 1 | 1 | |
| 9 | MS-119165 | Roller Presser Holder | 1 | 1 | |
| 10 | MS-173174 | Screw | 1 | 1 | |
| 11 | MS-025874 | Spring | 1 | 1 | |
| 12 | MS-054876 | Angle | 1 | 1 | |
| 13 | MS-130173 | Screw | 1 | 1 | |
| 14 | MS-175135 | Cover | 1 | 1 | |
| 15 | MS-700335 | Screw | 2 | 2 | |
| 16 | MS-069079 | Presser Foot Lifter | 1 | 1 | |
| 17 | MS-317950 | Screw | 1 | 1 | |
| 18 | MS-119004 | Bushing | 1 | 1 | |
| 19 | MS-118577 | Cam shaft | 1 | 1 | |
| 20 | MS-100331 | Screw | 1 | 1 | |
| 21 | MS-118535 | Presser Plate Spring | 1 | 1 | |
| 22 | MS-343901 | Screw | 1 | 1 | |
| 23 | MS-118105 | Stud | 1 | 1 | |
| 24 | MS-314286 | Screw | 1 | 1 | |
| 25 | MS-700017 | Screw | 1 | 1 | |
| 26 | MS-119016 | Spring | 1 | 1 | |
| 27 | MS-049657 | Presser Foot | 0 | 1 | |
| | MS-049657-1 | Presser Foot | 0 | 1 | |
| 28 | MS-108171 | Screw | 0 | 1 | |
| 29 | MS-118542 | Knee Lifter Connecting Lever | 1 | 1 | |
| 30 | MS-118536 | Spring Plate | 1 | 1 | |
| 31 | MS-118536-1 | Pin | 1 | 1 | |
| 32 | MS-118539 | Bushing | 1 | 1 | |
| 33 | MS-640150 | E-Ring | 1 | 1 | |
| 34 | MS-118536A | Lifting Lever Assy | 1 | 1 | (30~33) |
| 35 | MS-343902 | Bushing | 1 | 1 | |


TIMING BELT DRIVING MECHANISM FOR 9971 9974



TIMING BELT DRIVING MECHANISM FOR 9971 9974

| Ref. No | Part No. | Name of Part | Amt. req. | | Remarks |
|---------|-------------|-------------------|-----------|------|---------|
| | | | 9971 | 9974 | |
| 1 | MS-119097 | Plug | 2 | 2 | |
| 2 | MS-610300 | Retaining Ring | 1 | 1 | |
| 3 | MS-018624 | Ball Bearing | 2 | 2 | |
| 4 | MS-119707 | Timing Belt Wheel | 1 | 1 | |
| 5 | MS-335902-1 | Screw | 2 | 2 | |
| 6 | MS-335902 | Screw | 2 | 2 | |
| 7 | MS-119121 | Collar (Left) | 1 | 1 | |
| 8 | MS-700689 | Screw | 4 | 4 | |
| 9 | MS-018613 | Ball Bearing | 1 | 1 | |
| 10 | MS-119708 | Timing Belt Wheel | 1 | 1 | |
| 11 | MS-069161 | Timing Belt | 1 | 1 | |
| | MS-069161-1 | Timing Belt | 1 | 1 | |
| 12 | MS-119706 | Shaft | 1 | 1 | |
| 13 | MS-118726 | Collar (Right) | 1 | 1 | |


STITCH ADJUSTER MECHANISM



STITCH ADJUSTER MECHANISM

| Ref. No | Part No. | Name of Part | Amt. req. | | Remarks |
|---------|-------------------|----------------------------|-----------|------|---------|
| | | | 9971 | 9974 | |
| 1 | MS-175038 | Connecting Rod | 1 | 1 | |
| 2 | MS-6906 | Ball Bearing | 1 | 1 | |
| 3 | MS-175038A | Crank Rod Set | 1 | 1 | (1,2) |
| 4 | MS-215028 | Needle Bearing | 1 | 1 | |
| 5 | MS-118612 | Bearing Stud | 1 | 1 | |
| 6 | MS-165356 | Feeding Adjusting Plate | 1 | 1 | |
| 7 | MS-165356-1 | Screw | 1 | 1 | |
| 8 | MS-165356-8 | Nut | 1 | 1 | |
| 9 | MS-165356-5 | Spring | 1 | 1 | |
| 10 | MS-165356-7 | E-ring | 1 | 1 | |
| 11 | MS-165356-6 | Spring | 1 | 1 | |
| 12 | MS-165356-2 | Pin | 1 | 1 | |
| 13 | MS-165356-3 | Screw | 1 | 1 | |
| 14 | MS-175029 | Cam Assy | 1 | 1 | |
| 14-1 | MS-175029-1 | Stitch Regulating Seat | 1 | 1 | |
| 14-2 | MS-175029-2 | Stitch Regulating Fix Seat | 1 | 1 | |
| 14-3 | MS-175029-3 | Feed Adjusting Screw | 1 | 1 | |
| 14-4 | MS-175029-4 | Screw | 1 | 1 | |
| 14-5 | MS-175029-5 | Nut | 1 | 1 | |
| 14-6 | MS-175029-6 | Friction Plate | 1 | 1 | |
| 14-7 | MS-175029-7 | Screw | 1 | 1 | |
| 14-8 | MS-175029-8 | Screw | 1 | 1 | |
| 14-9 | MS-175029-9 | Screw | 1 | 1 | |
| 14-10 | MS-175029-10 | Eccentric wheel | 1 | 1 | |
| 14-11 | MS-175029-11 | Spring | 1 | 1 | |
| 14-12 | MS-175029-12 | Collar | 1 | 1 | |
| 14-13 | MS-175029-13 | Screw | 2 | 2 | |



FEED SHAFT MECHANISM



FEED SHAFT MECHANISM

| Ref. No | Part No. | Name of Part | Amt. req. | | Remarks |
|---------|-------------|----------------|-----------|------|---------|
| | | | 9971 | 9974 | |
| 1 | MS-610280 | Retaining Ring | 1 | 1 | |
| 2 | MS-119085 | Washer | 1 | 1 | |
| 3 | MS-133283 | Washer | 6 | 6 | |
| 4 | MS-215124 | Needle Bearing | 3 | 3 | |
| 5 | MS-118600 | Bushing | 1 | 1 | |
| 6 | MS-119163 | Crank | 1 | 1 | |
| 7 | MS-108225 | Screw | 1 | 1 | |
| 8 | MS-119164 | Clamp | 1 | 1 | |
| 9 | MS-108177 | Screw | 1 | 1 | |
| 10 | MS-119084 | Shaft | 1 | 1 | |
| 11 | MS-118601 | Bushing | 1 | 1 | |
| 12 | MS-119521 | Crank | 1 | 1 | |
| 13 | MS-130224 | Screw | 3 | 3 | |
| 14 | MS-335902-1 | Screw | 2 | 2 | |
| 15 | MS-119521-1 | Crank | 1 | 1 | |
| 16 | MS-700689 | Screw | 3 | 3 | |
| 17 | MS-118603 | Bushing | 1 | 1 | |
| 18 | MS-118893 | Collar | 1 | 1 | (16) |


CLUTCH SET MECHANISM



CLUTCH SET MECHANISM

| Ref. No | Part No. | Name of Part | Amt. req. | | Remarks |
|---------|------------|--------------------|-----------|------|------------|
| | | | 9971 | 9974 | |
| 1 | MS-175025 | Shaft | 1 | 1 | |
| 2 | MS-518250 | Retaining Ring | 1 | 1 | |
| 3 | MS-119711 | Shaft | 1 | 1 | |
| 4 | MS-175019 | Coupler | 1 | 1 | |
| 5 | MS-341901 | Screw | 4 | 4 | |
| 6 | MS-133109 | Connecting Plate | 1 | 1 | |
| 7 | MS-119081A | Safety Clutch | 1 | 1 | (7-1~7-14) |
| 7-1 | MS-700510 | Screw | 2 | 2 | |
| 7-2 | MS-173263 | Safety Clutch Seat | 1 | 1 | |
| 7-3 | MS-013153 | Spring | 2 | 2 | |
| 7-4 | MS-173261 | Latch | 1 | 1 | |
| 7-5 | MS-009408 | Hinge Stud | 1 | 1 | |
| 7-6 | MS-173264 | Coupler (right) | 1 | 1 | |
| 7-7 | MS-065052 | Pin | 2 | 2 | |
| 7-8 | MS-640150 | E - Ring | 1 | 1 | |
| 7-9 | MS-175023 | Stud | 2 | 2 | |
| 7-10 | MS-640130 | E- ring | 1 | 1 | |
| 7-11 | MS-013076 | Drop - In Pin | 1 | 1 | |
| 7-12 | MS-069037 | Washer | 1 | 1 | |
| 7-13 | MS-009343 | Spring | 1 | 1 | |
| 7-14 | MS-175126 | Ring | 1 | 1 | |
















BEDPLATE GEAR FEED MECHANISM FOR 9971



BEDPLATE GEAR FEED MECHANISM FOR 9971

| Ref. No | Part No. | Name of Part | Amt. req. | | Remarks |
|---------|-------------|------------------------|-----------|------|---------|
| | | | 9971 | 9974 | |
| 1 | MS-119795 | Roller Bracker | 1 | 0 | |
| 1-1 | MS-119795-1 | Roller Bracket (Upper) | 1 | 0 | |
| 1-2 | MS-119795-2 | Roller Bracket (Lower) | 1 | 0 | |
| 1-3 | MS-119795-3 | Screw | 1 | 0 | |
| 1-4 | MS-119795-4 | Screw | 1 | 0 | |
| 1-5 | MS-119795-5 | Ball | 24 | 0 | |
| 2 | MS-119737 | Bevel Gear | 1 | 0 | |
| 2-1 | MS-119737-1 | Roller Bracker | 1 | 1 | |
| 2-2 | MS-119737-2 | Roller Bracker | 1 | 1 | |
| 2-3 | MS-119737-3 | Feed Wheel | 1 | 0 | |
| 3 | MS-119723 | Bracket | 1 | 0 | |
| 3-1 | MS-119723-1 | Screw | 1 | 0 | |
| 3-2 | MS-119723-2 | Screw | 2 | 0 | |
| 4 | MS-119670 | Collar | 1 | 0 | |
| 4-1 | MS-119670-1 | Screw | 2 | 0 | |
| 5 | MS-119724 | Bushing | 1 | 0 | (1~5) |
| 6 | MS-119723A | Bevel Gear Assy | 1 | 0 | |
| 7 | MS-119535 | Bushing | 2 | 0 | |
| 8 | MS-119534 | Clutch | 1 | 0 | |
| 9 | MS-119535-1 | Screw | 4 | 0 | (7~(9) |
| 10 | MS-119535A | | 1 | 0 | |
| 11 | MS-119532 | Shaft | 1 | 0 | |
| 11-1 | MS-119535-1 | Screw | 2 | 0 | |
| 12 | MS-119533 | Bushing | 1 | 0 | |
| 13 | MS-5045 | Bevel Gear (Small) | 1 | 0 | |
| 14 | MS-5046 | Bevel Gear (Medium) | 1 | 0 | |
| 15 | MS-700689 | Screw | 4 | 0 | (13~15) |
| 16 | MS-175113 | | 1 | 0 | |

SPECIAL PARTS









15

16

SPECIAL PARTS

| Ref. No | Part No. | Name of Part | Amt. req. | | Remarks |
|---------|-------------|----------------------------|-----------|------|---------|
| | | | 9971 | 9974 | |
| 1 | MS-123456 | Accessory Bag | 1 | 1 | |
| 2 | MS-029836 | Vinyl Cover | 1 | 1 | |
| 3 | MS-800110 | Spanner | 1 | 1 | |
| 4 | MS-129915 | Screw Driver (Small) | 1 | 1 | |
| 5 | MS-029946 | Screw Driver (Middle) | 1 | 1 | |
| 6 | MS-029007 | Screw Driver (Large) | 1 | 1 | |
| 7 | MS-134356 | Needle | 10 | 10 | |
| 8 | MS-029394 | Oiler | 1 | 1 | |
| 9 | MS-119089-1 | Stitching Length Indicator | 1 | 1 | |
| 10 | MS-100355 | Screw | 1 | 1 | |
| 11 | MS-032808 | Head Cushion | 2 | 2 | |
| 12 | MS-010079 | Bobbin | 4 | 4 | |
| 13 | MS-259431 | Bobbin Winder | 1 | 1 | |
| 14 | MS-119026 | Spool Pin | 1 | 1 | |
| 15 | MS-FPL2 | Thread Stand (2-Pole) | 1 | 0 | |
| 16 | MS-FPL3 | Thread Stand (3-Pole) | 0 | 1 | |


ACCESSORIES FOR 9971 9974




ACCESSORIES FOR 9971 9974

| ef. No | Part No. | Name of Part | Amt. req. | | Remarks |
|--------|------------------|------------------------|-----------|------|---------|
| | | | 9971 | 9974 | |
| 1 | MS-171543 | Spring | 1 | 1 | |
| 2 | MS-171542 | Knee Lever Coupling | 1 | 1 | |
| 3 | MS-171413 | Knee Lever Rod | 1 | 1 | |
| 4 | MS-171412 | Knee Lever Assy | 1 | 1 | (2~4) |
| 5 | MS-171411 | Knee Lever Rod Assy | 1 | 1 | |
| 6 | MS-029934 | Hinge Connection Seat | 2 | 2 | |
| 7 | MS-030341 | Pin | 2 | 2 | |
| 8 | MS-029450 | Hinge Pin | 2 | 2 | |
| 9 | MS-118636 | Oil Pan | 1 | 1 | |
| 10 | MS-460157 | Screw | 6 | 6 | |
| 11 | MS-032717 | Head Rest Wood | 1 | 1 | |
| 12 | MS-032717-1 | Housing Support Stud | 1 | 1 | |
| 13 | MS-119078 | Belt Cover Set (Large) | 1 | 1 | |
| 13-1 | MS-119089-2 | Screw | 2 | 2 | |
| 14 | MS-119088 | Belt Cover Set (Small) | 1 | 1 | |
| 14-1 | MS-119078-1 | Screw | 2 | 2 | |


FOR 9974PRESSER FEET




474-1




474-2



474-3



474-4




474-5




474-6




474-7




474-8




474-9



474-10




474-11



474-K2

474-12
474 Garge



LP 9971 TD

&


LP 9974 TD

SPARE PARTS BOOK FOR TRIMMER DEVICE

B1

| Ref. No | Part No. | Name of Part | Amt. Req | | Remarks |
|---------|--------------|----------------------------------|----------|------|---------|
| | | | 9971 | 9974 | |
| 1 | MS-119766-2 | Thread Tension Regulator Assy | 1 | | |
| 2 | MS-119171-25 | Thread Tension Regulator Assy | | 1 | |
| 3 | MS-101022 | Rotary Solenoid | 1 | | |
| 1-1 | MS-119766-21 | Upper Thread Tension Plate | 1 | | |
| 1-2 | MS-119171-23 | Screw | 1 | | |
| 1-3 | MS-119766-1 | Thread Take-up Spring | 2 | | |
| 1-4 | MS-119766-22 | Thread Tension Stud | 1 | 1 | |
| 2-1 | MS-119171-1 | Nut | 1 | 2 | |
| 2-2 | MS-119171-2 | Spring Guide Assy | 1 | 2 | |
| 2-3 | MS-119171-3 | Tensin Spring | 1 | 1 | |
| 2-4 | MS-119171-4 | Thread Take-up Spring | 2 | 4 | |
| 2-5 | MS-119171-5 | Tensin Disc | 1 | 1 | |
| 2-6 | MS-119171-6 | Thread Tension Stud | 1 | 1 | |
| 2-7 | MS-119171-7 | Screw | 1 | 1 | |
| 2-8 | MS-119171-8 | Thread Tension Regulator Bushing | 1 | 1 | |
| 2-9 | MS-119171-9 | Tension Regulator Pin | | 1 | |
| 2-10 | MS-119171-10 | Tension Regulator Pin | 1 | 1 | |
| 2-11 | MS-119171-26 | Tension Regulator Plate | 2 | 2 | |
| 2-12 | MS-119171-27 | Screw | 1 | 1 | |
| 2-13 | MS-119171-13 | Tension Release Spring | 1 | 2 | |
| 2-14 | MS-119171-28 | Screw | | 1 | |
| 2-15 | MS-119171-29 | Upper Thread Tension Plate | 1 | 1 | |
| 2-16 | MS-119171-16 | Thread Tension Stud | 2 | 4 | |
| 2-17 | MS-119171-30 | Tensin Disc | 1 | 1 | |
| 2-18 | MS-119171-31 | Thread Tension Stud | | 2 | |
| 2-19 | MS-119171-32 | Spring | 1 | 1 | |
| 2-20 | MS-119171-33 | Thread Tension Stud | 1 | 1 | |
| 2-21 | MS-119171-34 | Thread Tension Stud | 1 | 1 | |
| 2-22 | MS-119171-22 | Tensin Spring | 1 | 2 | |
| 2-23 | MS-119171-35 | Nut | 2 | 2 | |
| 2-24 | MS-119171-24 | Screw | 1 | 1 | |


B2



B2

| Ref. No | Part No. | Name of Part | Amt. req. | Remarks |
|---------|-------------|---------------------------|-----------|---------|
| 1 | MS-101001 | Screw | 2 | 2 |
| 2 | MS-101002 | Washer | 2 | 2 |
| 3 | MS-101003 | Rotary Solenoid Seat Assy | 1 | 1 |
| 3-1 | MS-101003-1 | Rotary Solenoid Seat | 2 | 3-1~3-3 |
| 3-2 | MS-101003-2 | Cusion | 1 | 1 |
| 3-3 | MS-101003-3 | | 1 | 1 |
| 4 | MS-101004 | Screw | 2 | 2 |
| 5 | MS-101005 | Frame Plate | 1 | 1 |
| 6 | MS-101006 | Lever Shaft | 1 | 1 |
| 7 | MS-101007 | Screw | 2 | 2 |
| 8 | MS-101008 | Pin | 1 | 1 |
| 9 | MS-101009 | Lever Shaft | 1 | 1 |
| 10 | MS-101010 | Spring | 1 | 1 |
| 11 | MS-101011 | E- Ring | 1 | 1 |
| 12 | MS-101012 | Frame Plate | 1 | 1 |
| 13 | MS-101013 | Screw | 2 | 2 |
| 14 | MS-101014 | Lever Shaft | 1 | 1 |
| 15 | MS-101015 | Lever Shaft | 1 | 1 |
| 16 | MS-101016 | Lever Shaft | 1 | 1 |
| 17 | MS-101017 | Screw | 1 | 1 |
| 18 | MS-101018 | | 1 | 1 |
| 19 | MS-101019 | Screw | 1 | 1 |
| 20 | MS-101020 | Thread Retainer | 1 | 1 |
| 21 | MS-101021 | Washer | 1 | 1 |

(KNIFE ACTUATING MECHISM)




N1

| Ref. No | Part No. | Name of Part | Am't. req. | Remarks |
|---------|-----------|--------------------------------|------------|---------|
| 1 | MS-101023 | Frame Seat | 1 | 1 |
| 2 | MS-101024 | Screw | 2 | 2 |
| 3 | MS-101025 | Thread Trimming Solenoid Lever | 1 | 1 |
| 4 | MS-101026 | Screw | 1 | 1 |
| 5 | MS-101027 | Nut | 1 | 1 |
| 6 | MS-101028 | Screw | 1 | 1 |
| 7 | MS-101029 | Supporting Rod | 2 | 2 |
| 8 | MS-101030 | E-Ring | 4 | 4 |
| 9 | MS-101031 | Screw | 1 | 1 |
| 10 | MS-101032 | Rotary | 1 | 1 |
| 11 | MS-101033 | Knife Main Lever Shaft | 1 | 1 |
| 12 | MS-101034 | Spring | 1 | 1 |
| 13 | MS-101035 | Screw | 1 | 1 |
| 14 | MS-101036 | Cusion | 2 | 2 |
| 15 | MS-101037 | Nut | 1 | 1 |
| 16 | MS-101038 | Knife Main Lever Shaft | 1 | 1 |
| 17 | MS-101039 | Roller | 1 | 1 |
| 18 | MS-101040 | Screw | 1 | 1 |
| 19 | MS-101041 | Thread Trimming Cam | 1 | 1 |
| 20 | MS-101042 | Screw | 2 | 2 |
| 21 | MS-101043 | Washer | 1 | 1 |
| 22 | MS-101044 | Screw | 1 | 1 |
| 23 | MS-101045 | Rod end Bearing | 2 | 2 |
| 24 | MS-101037 | Nut | 2 | 2 |
| 25 | MS-101046 | Length Adjust Connecting Rod | 1 | 1 |
| 26 | MS-101047 | Frame Plate | 1 | 1 |
| 27 | MS-101048 | Screw | 1 | 1 |
| 28 | MS-101049 | Screw | 1 | 1 |
| 29 | MS-101050 | Thread Trimming Lever | 1 | 1 |
| 30 | MS-101051 | Spring | 1 | 1 |
| 31 | MS-101052 | Screw | 2 | 2 |
| 32 | MS-101053 | Positioning Block | 1 | 1 |
| 33 | MS-101054 | Frame Plate | 1 | 1 |


01

BEDPLATE FEED MECHANISM



| O1 | | Name of Parts | | Amt. Req. | | Remarks |
|----------|------------|----------------------|--|-----------|------|---------|
| Ref. No. | Parts No. | | | 9971 | 9974 | |
| 1 | MS-119145 | Cover Plate | | 1 | 0 | |
| 2 | MS-250084 | Screw | | 4 | 0 | |
| 3 | MS-119721 | Support Plate | | 1 | 0 | |
| 4 | MS-119144 | Washer | | 2 | 0 | |
| 5 | MS-130224 | Screw | | 2 | 0 | |
| 6 | MS-182451 | Screw | | 1 | 0 | |
| 7 | MS-119725 | Stud | | 1 | 0 | |
| 8 | MS-317170 | Screw | | 1 | 0 | |
| 9 | MS-135292 | Screw | | 4 | 0 | |
| 10 | MS-305174 | Washer | | 4 | 0 | |
| 11 | MS-168351 | Plug | | 1 | 0 | |
| 12 | MS-016120 | Ball Bearing | | 1 | 0 | |
| 13 | MS-119121 | Collar | | 1 | 0 | |
| 14 | MS-700689 | Screw | | 2 | 0 | |
| 15 | MS-305144 | Cover Plate | | 1 | 0 | |
| 16 | MS-101055 | Screw | | 2 | 0 | |
| 17 | MS-101056 | Needle Plate | | 1 | 0 | SM4-16 |
| 18 | MS-101057A | Needle Plate Bracket | | 1 | 0 | SM4-13 |
| 19 | MS-210168 | Screw | | 2 | 0 | |


LEFT SIDE BRACKET MECHANISM



| Q1. LEFT SIDE BRACKET MECHANISM | | | | | | | Amt. Req. | Remarks | Amt. Req. | Remarks |
|---------------------------------|-------------|-----------------------|----------|-------------|---------------|-----------|-----------|-----------|-----------|---------|
| Item No. | Parts No. | Name of Parts | Item No. | Parts No. | Name of Parts | Amt. Req. | Remarks | Amt. Req. | Remarks | |
| 1 | MS-101081 | Side Bracket | 30 | MS-101076-1 | PIN | 0 | SM3-2 | 0 | 1 | |
| 2 | MS-119499 | Cover Plate | 31 | MS-101076-2 | Hinge | 0 | | 0 | 1 | |
| 3 | MS-250084 | Screw | 32 | MS-101076-3 | Post Cap | 0 | | 0 | 1 | |
| 4 | MS-175318 | Stud | 33 | MS-108093 | Screw | 0 | | 0 | 1 | |
| 5 | MS-330217 | Screw | | MS-108086 | Electric Wire | 0 | | 0 | 1 | |
| 6 | MS-108093 | Screw | | | | 0 | | | | |
| 7 | MS-119143 | Spring Plate | | | | 0 | | | | |
| 8 | MS-101073 | Frame Plate | | | | 0 | SM4-1 | | | |
| 9 | MS-101070 | Screw | | | | 0 | SM4-24 | | | |
| 10 | MS-101068 | Screw | | | | 0 | SM4-25 | | | |
| 11 | MS-101069 | Fixed Knife | | | | 0 | SM4-4 | | | |
| 12 | MS-101071 | Screw | | | | 0 | | | | |
| 13 | MS-101072 | Spring Plate | | | | 0 | SM4-2 | | | |
| 14 | MS-101074 | Screw | | | | 0 | | | | |
| 15 | MS-135292 | Screw | | | | 0 | | | | |
| 16 | MS-305174 | Washer | | | | 0 | | | | |
| 17 | MS-119121 | Collar | | | | 0 | | | | |
| 18 | MS-700689 | Screw | | | | 0 | | | | |
| 19 | MS-016120 | Ball Bearing | | | | 0 | | | | |
| 20 | MS-119138-1 | Bearing Plate | | | | 0 | | | | |
| 21 | MS-119136-4 | Feed Wheel | | | | 0 | | | | |
| 22 | MS-119296 | Support Plate | | | | 0 | | | | |
| 23 | MS-108174-1 | Screw | | | | 0 | | | | |
| 24 | MS-108174-1 | Screw | | | | 0 | | | | |
| 25 | MS-100296 | Screw | | | | 0 | | | | |
| 26 | MS-101082 | Needle Plate SET(2.0) | | | | 0 | | | | |
| 27 | MS-101083 | Needle Plate | | | | 0 | SM3-17 | | | |
| 28 | MS-101084 | Needle Plate Bracket | | | | 0 | SM3-12 | | | |
| 29 | MS-101076 | Post Cap Assy | | | | 0 | | | | |

(LEFT BEDPLATE FEED MECHANISM)

R1-




RI

| Ref. No | Part No. | Name of Part | Amt. req. | Remarks |
|---------|--------------|------------------------------|-----------|-----------|
| 15 | MS-101058A | Hook Assy | 1 | 9971 9974 |
| 2 | MS-101058-1 | Bobbin Case | 1 | |
| 3 | MS-101058-2 | Screw | 2 | |
| 4 | MS-101058-3 | Spring | 1 | |
| 5 | MS-101058-4 | B/C Base | 1 | |
| 6 | MS-101058-5 | Screw | 2 | |
| 7 | MS-101058-6 | Hook Gid | 1 | |
| 8 | MS-101058-7 | Hook | 1 | |
| 9 | MS-101058-8 | Noodle Guard Washer | 1 | |
| 10 | MS-101058-9 | Screw | 2 | |
| 11 | MS-101058-10 | Bobbin Case Assy | 1 | |
| 12 | MS-101058-11 | Hook | 1 | |
| 13 | MS-101059 | Bobbin | 1 | |
| 14 | MS-100205 | Screw | 2 | |
| 15 | MS-119128 | Oil Felt | 1 | |
| 16 | MS-119127 | Rotating Hook Opener Bracket | 1 | |
| 17 | MS-101060 | Rotating Hook Opener | 1 | |
| 18 | MS-108093 | Screw | 2 | |
| 19 | MS-700689 | Screw | 2 | |
| 20 | MS-119494 | Driving Wheel | 1 | |
| 21 | MS-119105 | Washer | 1 | |
| 22 | MS-694ZZ | Ball Bearing | 1 | |
| 23 | MS-119106-1 | Driver | 1 | |
| 24 | MS-108177 | Screw | 1 | |
| 25 | MS-119106 | Driver | 1 | |
| 26 | MS-119105 | Washer | 1 | |
| 27 | MS-119525-1 | Hook Driver | 1 | |
| 28 | MS-119525 | Hook Shaft | 1 | |
| 29 | MS-215031 | Needle Bearing | 2 | |
| 30 | MS-215028 | Needle Bearing | 2 | |

| Ref. No | Part No. | Name of Part | Amt. req. | Remarks |
|---------|-------------|-----------------------|-----------|-----------|
| 31 | MS-119108 | Feed Wheel Shaft | 1 | 9971 9974 |
| 32 | MS-119104 | Pull-Off Shaft | 1 | |
| 33 | MS-119108-1 | Washer | 1 | |
| 34 | MS-141710 | Needle Bearing | 2 | |
| 35 | MS-119979 | Bushing | 1 | |
| 36 | MS-664390 | Retaining Ring | 1 | |
| 37 | MS-175138 | Bushing | 1 | |
| 38 | MS-119107-1 | Bushing | 1 | |
| 39 | MS-119950-1 | Screw | 1 | |
| 40 | MS-341901 | Screw | 2 | |
| 41 | MS-119947 | Washer | 1 | |
| 42 | MS-700689 | Screw | 10 | |
| 43 | MS-119109-1 | Bevel Gear | 1 | |
| 44 | MS-119109-2 | Bevel Gear | 1 | |
| 45 | MS-125010 | Washer | 1 | |
| 46 | MS-119133-1 | Bevel Gear | 1 | |
| 47 | MS-119133-2 | Bevel Gear | 1 | |
| 48 | MS-341901-1 | Screw | 2 | |
| 49 | MS-123778 | Collar | 1 | |
| 50 | MS-101061 | Screw | 1 | |
| 51 | MS-101062 | Movable Knife | 1 | |
| 52 | MS-101063 | Shaft | 1 | |
| 53 | MS-101064 | Bushing(upper) | 1 | |
| 54 | MS-101065 | Screw | 4 | |
| 55 | MS-101066 | Collar | 1 | |
| 56 | MS-101067 | Bushing(Lower) | 1 | |
| 57 | MS-101077 | Screw | 1 | |
| 58 | MS-101078 | Thread Trimming Lever | 1 | |
| 59 | MS-101079 | Connecting Rod | 1 | |
| 60 | MS-101080 | Screw | 1 | |

SI

(RIGHT SIDE BRACKET MECHISM)




SI

| Ref. No | Part No. | Name of Part | Amt. req. | | Remarks |
|---------|-------------|---------------|-----------|------|---------|
| | | | 9971 | 9974 | |
| 1 | MS-101068 | Screw | 1 | 1 | |
| 2 | MS-101069 | Fixed Knife | 1 | 1 | |
| 3 | MS-101070 | Screw | 1 | 1 | |
| 4 | MS-101071 | Screw | 1 | 1 | |
| 5 | MS-101072 | Spring Plate | 1 | 1 | |
| 6 | MS-101073 | Frame Plate | 1 | 1 | |
| 7 | MS-101074 | Screw | 2 | 2 | |
| 8 | MS-101075 | Side Bracket | 1 | 1 | |
| 9 | MS-119143 | Spring Plate | 1 | 1 | |
| 10 | MS-108093 | Screw | 1 | 1 | |
| 11 | MS-135292 | Screw | 4 | 4 | |
| 12 | MS-305174 | Washer | 4 | 4 | |
| 13 | MS-330217 | Screw | 1 | 1 | |
| 14 | MS-175318 | Stud | 1 | 1 | |
| 15 | MS-700336 | Screw | 1 | 1 | |
| 16 | MS-250084 | Screw | 2 | 2 | |
| 17 | MS-175234 | Screw | 1 | 1 | |
| 18 | MS-700689 | Screw | 2 | 2 | |
| 19 | MS-119121 | Collar | 1 | 1 | |
| 20 | MS-016120 | Ball Bearing | 1 | 1 | |
| 21 | MS-101076 | Post Cap Assy | 1 | 1 | |
| 22 | MS-108093 | Screw | 2 | 2 | |
| 23 | MS-101076-1 | Pin | 1 | 1 | |
| 24 | MS-101076-2 | Hinge | 1 | 1 | |
| 25 | MS-101076-3 | | 1 | 1 | |

(RIGHT BEDPLATE FEED MECHANISM)

U1




U1

| Ref. No | Part No. | Name of Part | Amt. req. | | Remarks |
|---------|--------------|----------------------------|-----------|------|----------|
| | | | 9971 | 9974 | |
| 1 | MS-101058A | Hook Assy | 1 | 1 | |
| 2 | MS-101058-1 | Bobbin Case | 1 | 1 | |
| 3 | MS-101058-2 | Screw | 2 | 2 | |
| 4 | MS-101058-3 | Spring | 1 | 1 | |
| 5 | MS-101058-4 | B/C Base | 1 | 1 | |
| 6 | MS-101058-5 | Screw | 2 | 2 | |
| 7 | MS-101058-6 | Hook Gid | 1 | 1 | |
| 8 | MS-101058-7 | Hook | 1 | 1 | |
| 9 | MS-101058-8 | Noodle Guard Washer | 1 | 1 | |
| 10 | MS-101058-9 | Screw | 2 | 2 | |
| 11 | MS-101058-10 | Bobbin Case Assy | 1 | 1 | |
| 12 | MS-101058-11 | Hook | 1 | 1 | |
| 13 | MS-101059 | Bobbin | 1 | 1 | |
| 14 | MS-100205 | Screw | 1 | 1 | |
| 15 | MS-119128 | Oil Felt | 1 | 1 | |
| 16 | MS-119127 | Rotating Hook Opener Brack | 1 | 1 | |
| 17 | MS-101060 | Rotating Hook Opener | 1 | 1 | SM2-3.18 |
| 18 | MS-108093 | Screw | 2 | 2 | |
| 19 | MS-694ZZ | Ball Bearing | 1 | 1 | |
| 20 | MS-119106-1 | Driver | 1 | 1 | |
| 21 | MS-108177 | Screw | 1 | 1 | |
| 22 | MS-119106 | Driver | 1 | 1 | |
| 23 | MS-119105 | Washer | 1 | 1 | |
| 24 | MS-119525-1 | Hook Driver | 1 | 1 | |
| 25 | MS-125010 | Washer | 1 | 1 | |
| 26 | MS-119525 | Hook Shaft | 1 | 1 | |
| 27 | MS-215031 | Needle Bearing | 2 | 2 | |
| 28 | MS-215028 | Needle Bearing | 2 | 2 | |

| Ref. No | Part No. | Name of Part | Amt. req. | | Remarks |
|---------|-------------|--------------------|-----------|------|----------|
| | | | 9971 | 9974 | |
| 29 | MS-119524 | Feed Wheel Shaft | 1 | 1 | |
| 30 | MS-119979 | Bushing | 1 | 1 | |
| 31 | MS-664390 | Retaining Ring | 1 | 1 | |
| 32 | MS-175138 | Bushing | 1 | 1 | |
| 33 | MS-119107-1 | Bushing | 1 | 1 | SM2-3.14 |
| 34 | MS-119950-1 | Screw | 1 | 1 | SM2-3.2 |
| 35 | MS-341901 | Screw | 2 | 2 | |
| 36 | MS-119947 | Washer | 1 | 1 | |
| 37 | MS-119133-1 | Bevel Gear (Small) | 1 | 1 | |
| 38 | MS-119133-2 | Bevel Gear (Large) | 1 | 1 | |
| 39 | MS-341901-1 | Screw | 2 | 2 | |
| 40 | MS-700689 | Screw | 4 | 4 | |
| 41 | MS-123778 | Collar | 1 | 1 | |
| 42 | MS-101061 | Screw | 1 | 1 | |
| 43 | MS-101062 | Movable Knife | 1 | 1 | SM4-5 |
| 44 | MS-101063 | Shaft | 1 | 1 | SM2-3.3 |
| 45 | MS-101064 | Bushing(upper) | 1 | 1 | SM2-3.6 |
| 46 | MS-101065 | Screw | 4 | 4 | |
| 47 | MS-101066 | Collar | 1 | 1 | SM2-3.5 |
| 48 | MS-101067 | Bushing(Lower) | 1 | 1 | SM2-3.4 |

ELECTRIC WARE ASSEMBLING CHART




| Ref. No | Part No. | Name of Part | Ant. req. | | Remarks |
|---------|-----------|-------------------------------|-----------|------|---------|
| | | | 9971 | 9974 | |
| 1 | MS-101087 | Screw | 5 | 5 | |
| 2 | MS-101088 | Fix Clip For Power Cable | 5 | 5 | |
| 3 | MS-101089 | Power Live Connector | 2 | 2 | |
| 4 | MS-101090 | Screw | 2 | 2 | |
| 5 | MS-101091 | Protect Cover For Power Cable | 2 | 2 | |
| 6 | MS-101092 | Fix Braket For Power Cable | 1 | 1 | |
| 7 | MS-101093 | Power Plug | 1 | 1 | |
| | | | 9971 | 9974 | |

LP 9971 AUT

SPARE PARTS BOOK FOR BACKTACKING DEVICE


C1




| Ref No | Part No. | Name of Part | 9971-TD/aut | Amt. Req. | Remarks |
|---------|-------------|--------------------|-------------|-----------|---------|
| CI-30 | MS-102026 | Bearing Bracket | 1 | | |
| CI-31 | MS-102027 | Bearing Set | 1 | | |
| CI-32 | MS-102005 | Ring | 2 | | |
| CI-33 | MS-102006 | Rod End Bearing | 1 | | |
| CI-34 | MS-102028 | Bearing Bracket | 1 | | |
| CI-35 | MS-130224 | Screw | 2 | | |
| CI-36 | MS-102029 | Connection Rod Set | 1 | | |
| CI-37 | MS-102030 | Clamp(Upper) | 1 | | |
| CI-37-1 | MS-174173 | Screw | 1 | | |
| CI-38 | MS-102031 | Connection Block | 1 | | |
| CI-39 | MS-102032 | Clamp(Lower) | 1 | | |
| CI-40 | MS-102033 | Pin | 2 | | |
| CI-41 | MS-102034 | Spring | 1 | | |
| CI-42 | MS-102035 | Shaft | 1 | | |
| CI-43 | MS-102033-1 | Pin | 1 | | |

| Ref No | Part No. | Name of Part | 9971-TD/aut | Amt. Req. | Remarks |
|---------|-------------|-----------------|-------------|-----------|---------|
| CI-1 | MS-119507 | Link | 2 | | 3-9 |
| CI-2 | MS-174176 | Screw | 4 | | 3-10 |
| CI-3 | MS-119087 | Oil Felt | 4 | | 3-11 |
| CI-4 | MS-102001 | Bearing Set | 1 | | |
| CI-5 | MS-102002 | Fixed Seat | 1 | | |
| CI-6 | MS-102003 | Bearing Bracket | 1 | | |
| CI-7 | MS-102004 | Pin | 1 | | |
| CI-8 | MS-102005 | Ring | 2 | | |
| CI-9 | MS-102006 | Rod End Bearing | 1 | | |
| CI-10 | MS-130224 | Screw | 2 | | |
| CI-11 | MS-102007 | Washer | 1 | | |
| CI-11-1 | MS-102007-1 | Washer | 1 | | |
| CI-12 | MS-102008 | Ring | 3 | | |
| CI-13 | MS-102009 | Washer | 3 | | |
| CI-13-1 | MS-102009-1 | Washer | 1 | | |
| CI-14 | MS-102010 | Free Bearing | 1 | | |
| CI-15 | MS-102011 | Free - Wheeling | 1 | | |
| CI-16 | MS-102012 | Needle Bearing | 1 | | |
| CI-17 | MS-102013 | Free Bearing | 1 | | |
| CI-18 | MS-102014 | Free - Wheeling | 1 | | |
| CI-19 | MS-102015 | Bushing | 1 | | |
| CI-20 | MS-102016 | Shaft Set | 1 | | |
| CI-21 | MS-102017 | Ball | 1 | 3.5 | |
| CI-22 | MS-102018 | Bushing | 1 | | |
| CI-23 | MS-102019 | Shaft | 1 | | |
| CI-24 | MS-102020 | Ball | 3 | 2 | |
| CI-25 | MS-102021 | Spring | 1 | | |
| CI-26 | MS-102022 | Washer | 1 | | |
| CI-27 | MS-102023 | Shaft | 1 | | |
| CI-28 | MS-102024 | Bearing | 1 | 51100A | |
| CI-29 | MS-102025 | Bearing Bracket | 1 | | |

G1






| Ref No | Part No. | Name of Part | 9971-TD/aut | Amt. Req. | Remarks |
|--------|-------------|----------------------|-------------|-----------|---------|
| G1-1 | MS-102036 | Nut | | 2 | |
| G1-2 | MS-102037 | Screw | | 1 | |
| G1-3 | MS-102038 | Bushing | | 2 | |
| G1-4 | MS-102039 | Spring Plate | | 1 | |
| G1-5 | MS-102040 | Nut | | 2 | |
| G1-6 | MS-102041 | E-Ring | | 1 | |
| G1-7 | MS-102042 | Stud | | 1 | |
| G1-8 | MS-102043 | Screw | | 1 | |
| G1-9 | MS-174176 | Screw | | 1 | |
| G1-10 | MS-102044 | Collar | | 1 | |
| G1-11 | MS-314946 | Screw | | 2 | |
| G1-13 | MS-102046 | Connection Rod | | 1 | |
| G1-14 | MS-108225 | Screw | | 1 | |
| G1-15 | MS-102047 | Pin | | 1 | |
| G1-16 | MS-102048 | Connection Plate | | 1 | |
| G1-17 | MS-102049 | E-Ring | | 2 | |
| G1-18 | MS-102050 | Needle Bearing | | 3 | |
| G1-19 | MS-102051 | Shaft | | 1 | |
| G1-20 | MS-102052 | Fixed Seat | | 1 | |
| G1-21 | MS-130224 | Screw | | 1 | |
| G1-22 | MS-119163 | Crank | | 1 | |
| G1-23 | MS-108225 | Screw | | 1 | |
| G1-24 | MS-133283 | Washer | | 2 | |
| G1-25 | MS-215124 | Needle Bearing | | 2 | |
| G1-26 | MS-118600 | Bushing | | 2 | |
| G1-27 | MS-119511-1 | Under Shaft | | 1 | |
| G1-28 | MS-118504 | Collar | | 1 | |
| G1-29 | MS-118503 | Screw | | 2 | |
| G1-30 | MS-610370 | C-Ring | | 1 | |
| G1-31 | MS-119042-2 | Eccentric With Rod | | 1 | |
| G1-32 | MS-215028 | Needle Bearing | | 1 | |
| G1-33 | MS-175150 | Pin | | 1 | |
| G1-34 | MS-242810 | Needle Bearing | | 1 | |
| G1-35 | MS-119042 | Crank With Eccentric | | 1 | |
| G1-36 | MS-108225-2 | Screw | | 1 | |
| G1-37 | MS-130224 | Screw | | 1 | |



G2

| Ref No | Part No. | Name of Part | Am. Req. | TD/aut | Remarks |
|--------|--------------|----------------|----------|--------|---------|
| G2-1 | MS-102053 | Crank | 1 | | |
| G2-2 | MS-130224 | Screw | 1 | | |
| G2-3 | MS-102054 | Washer | 2 | | |
| G2-4 | MS-102055 | Connection Rod | 1 | | |
| G2-5 | MS-215028 | Needle Bearing | 4 | | |
| G2-6 | MS-102116 | Pin | 1 | | |
| G2-7 | MS-102056 | Connection Rod | 1 | | |
| G2-8 | MS-102118 | Pin | 1 | | |
| G2-9 | MS-102057 | Waving Seat | 1 | | |
| G2-10 | MS-130224-1 | Screw | 6 | | |
| G2-11 | MS-119046 | Connecting Rod | 1 | | |
| G2-12 | MS-102117 | Pin | 1 | | |
| G2-13 | MS-102058 | Connecting Rod | 1 | | |
| G2-14 | MS-108294 | Screw | 1 | | |
| G2-15 | MS-102059 | Top Rod Seat | 1 | | |
| G2-16 | MS-119078-1 | Screw | 1 | | |
| G2-17 | MS-102060 | Waving Arm | 1 | | |
| G2-18 | MS-102061 | Rod | 1 | | |
| G2-19 | MS-130224 | Screw | 1 | | |
| G2-20 | MS-102062 | Washer | 2 | | |
| G2-21 | MS-102063 | Support Plate | 1 | | |
| G2-22 | MS-102064 | Shaft | 1 | | |
| G2-23 | | Screw | 1 | | |
| G2-24 | MS-165356-1B | Screw | 1 | | |
| G2-25 | MS-305305-1 | Scrcw | 1 | | |
| G2-26 | MS-165356-8 | Nut | 2 | | |


G3



| Ref No | Part No. | Name of Part | 9971-TD/aut | Amt. Req. TD/aut | Remarks |
|--------|-------------|----------------------|-------------|------------------|---------|
| 13-1 | MS-102065 | Reverse Sewing Lever | | 1 | |
| 13-2 | MS-700689 | Screw | | 2 | |
| 13-3 | MS-102066 | Fixed Bushing | | 1 | |
| 13-4 | MS-102066-1 | Screw | | 3 | |
| 13-5 | MS-102067 | Shaft | | 1 | |
| 13-6 | MS-102068 | Spring | | 1 | |
| 13-7 | MS-102069 | Shaft | | 1 | |
| 13-8 | MS-102070 | Fixed Seat | | 1 | |
| 13-9 | MS-130224 | Screw | | 1 | |
| 13-10 | MS-102071 | Pin | | 3 | |
| 13-11 | MS-102072 | Washer | | 2 | |
| 13-12 | MS-102073 | A Djusting Stud | | 1 | |
| 13-13 | MS-102074 | Waving Plate | | 3 | |
| 13-14 | MS-102049 | Ring | | | G1-17 |


BEDPLATE₂ FEED MECHANISM

01




| O1. NEEDLE PLATE FRAME MECHANISM | | | | | |
|----------------------------------|------------|----------------------|-------------|---|---------|
| Ref. No. | Parts No. | Name of Parts | Amt. Req. | | Remarks |
| | | | 9971-TD/aut | | |
| O1-1 | MS-119145 | Cover Plate | 1 | 0 | |
| O1-2 | MS-250084 | Screw | 4 | 0 | |
| O1-3 | MS-119721 | Support Plate | 1 | 0 | |
| O1-4 | MS-119144 | Washer | 2 | 0 | |
| O1-5 | MS-130224 | Screw | 2 | 0 | |
| O1-6 | MS-182451 | Screw | 1 | 0 | |
| O1-7 | MS-119725 | Stud | 1 | 0 | |
| O1-8 | MS-317170 | Screw | 1 | 0 | |
| O1-9 | MS-135292 | Screw | 4 | 0 | |
| O1-10 | MS-305174 | Washer | 4 | 0 | |
| O1-11 | MS-168351 | Plug | 1 | 0 | |
| O1-12 | MS-016120 | Ball Bearing | 1 | 0 | |
| O1-13 | MS-119121 | Collar | 1 | 0 | |
| O1-14 | MS-700689 | Screw | 2 | 0 | |
| O1-15 | MS-305144 | Cover Plate | 1 | 0 | |
| O1-16 | MS-101055 | Screw | 2 | 0 | |
| O1-17 | MS-101056 | Needle Plate | 1 | 0 | |
| O1-18 | MS-101057A | Needle Plate Bracket | 1 | 0 | |
| O1-19 | MS-210168 | Screw | 2 | 0 | |

03



| Ref No | Part No. | Name of Part | 9971-TD/aut | Ami. Req. | Remarks |
|--------|-------------|-----------------|-------------|-----------|---------|
| 03-1 | MS-102095 | Connection Seat | | 3 | |
| 03-2 | MS-102096 | Connection Rod | | 1 | |
| 03-3 | MS-102097 | Waving Arm | | 1 | |
| 03-4 | MS-130224 | Screw | | 1 | |
| 03-5 | MS-102098 | Rod | | 1 | |
| 03-6 | MS-102099 | Fixed Bushing | | 3 | |
| 03-7 | MS-102066-1 | Screw | | 1 | |
| 03-8 | MS-102100 | Waving Arm | | 1 | |
| 03-9 | MS-130224 | Screw | | 1 | |
| 03-10 | MS-102101 | Connection Rod | | 1 | |
| 03-11 | MS-102102 | Washer | | 1 | |
| 03-12 | MS-102103 | Spring | | 1 | |
| 03-13 | MS-102104 | Fixed Plate Set | | 1 | |
| 03-14 | MS-102105 | Presser Plate | | 1 | |
| 03-15 | MS-102106 | Fixed Seat | | 1 | |
| 03-16 | MS-102107 | Pin | | 1 | |
| 03-17 | MS-102109 | Adjusting Stud | | 1 | |
| 03-18 | MS-119092-1 | Bracket | | 1 | |
| 03-19 | MS-119092-2 | Screw | | 2 | |



| Ref No | Part No. | Name of Part | Amt. Req. 9971-TD/aut | Remarks |
|--------|-------------|-----------------------|--------------------------|---------|
| O2-32 | MS-119216-1 | Housing Front Section | 1 | |
| O2-33 | MS-119216-2 | Screw | 2 | |

| Ref No | Part No. | Name of Part | Amt. Req. 9971-TD/aut | Remarks |
|--------|-----------|-----------------------|--------------------------|---------|
| O2-1 | MS-102075 | Suppling Waving Arm | 1 | |
| O2-2 | MS-102076 | Suppling Waving Arm | 1 | |
| O2-3 | MS-101077 | Suppling Waving Arm | 1 | |
| O2-4 | MS-102078 | Suppling Waving Arm | 1 | |
| O2-5 | MS-130224 | Screw | 4 | |
| O2-6 | MS-174176 | Screw | 8 | |
| O2-7 | MS-119087 | Oil Felt | 8 | |
| O2-8 | MS-102079 | Link | Z | |
| O2-9 | MS-102080 | Link | 1 | |
| O2-10 | MS-102081 | Link | 2 | |
| O2-11 | MS-102082 | Free Bearing | 2 | |
| O2-12 | MS-102083 | Free Bearing | 1 | |
| O2-13 | MS-102084 | Free Bearing | 1 | |
| O2-15 | MS-102012 | Needle Bearing | 4 | |
| O2-16 | MS-102086 | Free- Wheeling | 2 | |
| O2-17 | MS-102087 | Free- Wheeling | 1 | |
| O2-18 | MS-102088 | Free- Wheeling | 1 | |
| O2-20 | MS-102089 | Bearing | 2 | |
| O2-21 | MS-102090 | Washer | 2 | |
| O2-22 | MS-102091 | Shaft Set | 1 | |
| O2-23 | MS-102092 | Bushing | 1 | |
| O2-24 | MS-102092 | Bushing | 1 | |
| O2-25 | MS | Ball MS-102017 | 1 | |
| O2-26 | MS-102018 | Bushing | 1 | |
| O2-27 | MS-102093 | Shaft | 1 | |
| O2-28 | MS-102020 | Ball | 3 | |
| O2-29 | MS-102021 | Spring | 1 | |
| O2-30 | MS-102022 | Washer | 1 | |
| O2-31 | MS-102094 | Shaft | 1 | |