



100% MADE IN ITALY



POWERFUL,  
LIGHT, EASY.

# FP503MT NEW PNEUMATIC HAND SHEAR

FP503MT. - The smallest and powerful pneumatic shear for edge trimming.



1946



### WHAT'S NEW:

Central back-located air exhaust  
Integrated slim foot for edge trimming  
Integrated welded counterblade  
High manageability in 780 g

### FOLLOW US:




#### RASOR ELETTROMECCANICA SRL

Via Vincenzo Caldesi 6 • 20161 Milan • Italy  
ph. +39 02 66 22 12 31 • fax +39 02 66 22 12 93  
info@rasor-cutters.com

www.rasor-cutters.com

# NEW PNEUMATIC HAND SHEAR FP503MT



minimum recommended



Rasor recommend to use only dry air lubricated  
with special Rasor VG 5 pneumatic oil

### TECHNICAL DETAILS:

Muffled turbine motor with central back-located air exhaust  
6 bar nominal\* ( $\pm 1$  bar) lubricated air supply

**Air consumption:** 9 std liters/sec\*

**Power:** 350 W at nominal air supply conditions

**Blade:** 50 mm with hard metal counterblade

**Blade descr.:** 50SHSS, 50 mm dia., 7-edge, HSS steel

**Blade speed:** 1900 r.p.m.\*

**Cutting ability:** up to 8 mm

**Sound pressure:** 72 dB<sub>e</sub> (EN ISO 15744)\*

**Vibration Level:** 1,36 m/sec<sup>2</sup> (ISO 8662)\*

**Net weight:** 780 g

**Total weight (with packing):** 1600 g

**Temperature range:** 0 – 55 C

**Umidity range:** 10 – 95% without condensate

\*The reported data are collected at a pressure of 6 bar (ISO 2787: 1984), recommended operating pressure.